

**Electric Puller** 

60

**UTT15W** 



**ELECTRIC PULLER** 3,300LB

## **Kraft Series**

#### Kraft means Force.

The Stärke Kraft includes German engineering and design aspects which power over the competition in strength, versatility and usability. This electric puller tug was ergonomically designed as a compact, easy to maneuver unit capable of pulling up to 3,300 lbs across your warehouse, factory or distribution facility.

**FEATURES** 

**Towing Capacity** • 3300 lbs

Wheels

• Front - Pneumatic

• Back - Rubber

Weight with Battery

• 330 lbs

#### Battery

- Built-in charger
- 24/80aH

#### Controls

- Fingertip control
- Emergency stop device
- Step-less speed control

#### Frame

- Compact design, built for easy
- Ergonomically designed handle
- Length 66.7"
- Width 28.4"
- Turning radius 50.8"

Powertrain/electrical


- DC brushless motor
- Travel speed 3.4 mph unloaded, 3 mph loaded





#### sales@superlift.net 1-800-884-1891 www.superlift.net

uller	Stärke Kraft		Mobile TUG 15	A	DS Xpres
ow Capacity	3,300 lbs		1,500 lbs		1,500
awbar Pull	300 lbs		N/A		250 lk
, id			490		u.
Kraft Electric Puller			UTT15W	70	
apacity		lbs	3,300		
ated Drawbar Pull		Ν	300		
Vheelbase		y (in)	15.6		
xle loading, unladen	Front	lbs	235.4	4	Ommer B
xle loading, unladen	Rear	lbs	94.6		
ire Size	Front, pneumatic		16 x 6.5-8.00		
	Rear, rubber		5.0		ЪĹК
Vheels, number front/rear (x=drive wheel	s)		2x/1		FT.
read	Front	b10 (in)	21.9		
leight of Tiller in drive position		h14 (in)	35.0		
eraw Chassis height		h10 (in)	7.0 x 8.6 x 10.2		
overall length		l1 (in)	66.7		<i> </i> -
overall width		b1 (in)	28.4	11	
iround clearance		m2 (in)	3.9		·
urning radius		Wa (in)	50.8		
ravel Speed	Laden	mph	3.0		- 1/
ravel Speed	Unladen	mph	3.4		0 0
prawbar pull	Laden/Unladen	N	300		
prawbar pull (max)	Laden/Unladen	Ν	1000		
rake			electric		
attery Voltage		v/Ah	24/80		
attery Weight		lbs	107.8		
attery Dimensions	L x W x H	in	10.2 x 6.7 x 8.5		b10
					010
ype of Drive Control			mosfet		
ype of Drive Control attery Compartment Size		in	mosfet 10.6 x 7.0 x 8.9	_	b1



ow Capacity3,300 lbs1,500 lbsrawbar Pull300 lbsN/AImage: Second	Why Ch	noose a Stärke	Kraf	f <mark>t over</mark> a
rawbar Pull 300 lbs N/A    rawbar Pull 300 lbs N/A   Image: State of the	Puller	Stärke Kraft		Mobile TUG 1
Kraft Electric Puller UTTI5W   apacity Ibs 3,300   ated Drawbar Pull N 3,000   vheelbase y (in) 15,6   xile loading, unladen Front, pneumatic 16 × 6,5-8,00   Rear, rubber 16 × 6,5-8,00 9,4,6   ire Size Front, pneumatic 16 × 6,5-8,00   Rear, rubber 16 × 6,5-8,00 2x/1   read Front, pneumatic 16 × 6,5-8,00   read Front, bl0 (in) 21,9   eight of Tiller in drive position h14 (in) 35,0   read Front bl0 (in) 2,9   werall length II (in) 6,6,7   voreall width II (in) 6,6,7   voreall width II (in) 3,9   urning radius Wa (in) 50,8   ravel Speed Laden /Unladen N   rawbar pull Laden/Unladen N   rawbar pull Laden/Unladen N   rawbar pull Laden/Unladen N   rawbar pull Laden/Unladen N   100,2 x 6,7 x 8,5 m	Tow Capacity	3,300 lbs		1,500 lbs
Image: constraint of the second se	Drawbar Pull	300 lbs		N/A
apacityIbs3,300ated Drawbar PullN300Vheelbasey (in)15.6xle loading, unladenFrontlbs235.4xle loading, unladenRearlbs94.6ire SizeFront, pneumatic16 × 6.5-8.00Rear, rubberC16 × 6.5-8.00Rear, rubberb10 (in)21.9readFrontb10 (in)21.9eight of Tiller in drive positionb10 (in)7.0 × 8.6 × 10.2reverall lengthh10 (in)7.0 × 8.6 × 10.2verall lengthb11 (in)66.7verall widthb11 (in)28.4round clearancem2 (in)3.9urning radiusWa (in)50.8ravbel SpeedUnladenmphravbar pull (max)Laden/UnladenNravbar pull (max)Laden/UnladenNravbar pull (max)Laden/UnladenNravbar pull (max)Laden/UnladenNravbar pull (max)Laden/UnladenNravbar pull (max)Laden/UnladenNattery Voltageu/A10.2 × 6.7 × 8.5ype of Drive ControlLa W x Hin10.2 × 6.7 × 8.5ype of Drive ControlinN10.6 × 7.0 × 8.9				490
ated Drawbar Pull N 300   Vheelbase y (in) 15.6   ixle loading, unladen Front Ibs 94.6   ire Size Front, pneumatic 16 × 6.5-8.00   Vheels, number front/rear (x=drive wheels) 70 16 × 6.5-8.00   read Front, pneumatic 2x/1   read Front b10 (in) 21.9   eight of Tiller in drive position h10 (in) 7.0 × 8.6 × 10.2   raw Chassis height h10 (in) 7.0 × 8.6 × 10.2   raw Chassis height h10 (in) 7.0 × 8.6 × 10.2   raw Chassis height b1 (in) 28.4   round clearance m2 (in) 3.9   urang radius Wa (in) 3.0   ravel Speed Laden/Unladen mph   rawbar pull (max) Laden/Unladen N   rawbar pull (max) Laden/Unladen N   rake ibls 10.7.8   attery Voltage k × M × H in   attery Voltage k × M × H in   attery Dimensions k × W × H in in.2 × 6.7 × 8.5   y	Kraft Electric Puller			UTT15W
v/heelbase y (in) 15.6   xle loading, unladen Front Ibs 235.4   xle loading, unladen Rear Ibs 94.6   resize Front, pneumatic Ibs 16 × 6.5-8.00   Rear, rubber Rear, rubber 5.0   vheels, number front/rear (x=drive wheels) Front b10 (in) 2x/1   read Front b10 (in) 21.9   eight of Tiller in drive position h14 (in) 35.0   raw Chassis height h10 (in) 7.0 × 8.6 × 10.2   werall length I1 (in) 66.7   werall width b1 (in) 28.4   round clearance m2 (in) 3.9   urning radius Wa (in) 50.8   ravel Speed Unladen mph   ravel Speed Unladen N   rawbar pull (max) Laden/Unladen N   rake in 1000   rake in 102 × 6.7 × 8.5   utery Voltage L x W x H in 10.2 × 6.7 × 8.5   ype of Drive Control K mosfet mosfet	Capacity		lbs	3,300
xle loading, unladenFront Rearlbs235.4xle loading, unladenRearlbs94.6ire SizeFront, pneumatic16 × 6.5-8.00Rear, rubber5.0Vheels, number front/rear (x=drive wheels)2x/1readFrontb10 (in)21.9eight of Tiller in drive positionh14 (in)3500rraw Chassis heighth10 (in)7.0 × 8.6 × 10.2verall lengthl1 (in)66.7verall widthb1 (in)28.4round clearancem2 (in)3.9urning radiusWa (in)50.8ravel SpeedLadenmphvarabar pullLaden/UnladenNrawbar pull (max)Laden/UnladenNrakeibs107.8attery VoltageL x W x Hinattery DimensionsL x W x Hinattery Compartment Sizein10.6 × 7.0 × 8.9	Rated Drawbar Pull		Ν	300
xkle loading, unladen Rear Ibs 94.6   ire Size Front, pneumatic 16 × 6.5-8.00   Rear, rubber Kear, rubber 5.0   vheels, number front/rear (x=drive wheels) Front b10 (in) 2x/1   read Front b10 (in) 21.9   eight of Tiller in drive position h14 (in) 35.0   var Chassis height h10 (in) 7.0 × 8.6 × 10.2   verall length h10 (in) 7.0 × 8.6 × 10.2   verall length h10 (in) 7.0 × 8.6 × 10.2   verall width b1 (in) 66.7   verall width b1 (in) 28.4   verall speed b1 (in) 3.9   urning radius Wa (in) 50.8   ravel Speed Unladen mph   varabar pull (max) Laden/Unladen N   varabar pull (max) Laden/Unladen N 1000   rake ibs 107.8 10.2 × 6.7 × 8.5   attery Voltage Lx W x H in 10.2 × 6.7 × 8.5   ype of Drive Control K mosfet mosfet	Wheelbase		y (in)	15.6
Front, pneumatic   If k x 6.5-8.00     Rear, rubber   5.0     Vheels, number front/rear (x=drive wheels)   10     read   Front   b10 (in)   2x/1     read   Front   b10 (in)   21.9     eight of Tiller in drive position   h14 (in)   35.0     raw Chassis height   h10 (in)   7.0 x 8.6 x 10.2     werall length   11 (in)   66.7     werall width   b1 (in)   28.4     word clearance   m2 (in)   3.9     urning radius   Wa (in)   50.8     ravel Speed   Unladen   mph   3.4     ravel Speed   Unladen   N   300     wrawbar pull (max)   Laden/Unladen   N   1000     rake   in   10.2 x 6.7 x 8.5   107.8     attery Voltage   ki k with k in   10.2 x 6.7 x 8.5   107.8     word Chronol   ki k in   10.2 x 6.7 x 8.5   107.8	Axle loading, unladen	Front	lbs	235.4
Rear, rubberRear, rubber5.0Vheels, number front/rear (x=drive wheels) $5.0$ $2x/1$ readFront $b10$ (in) $21.9$ leight of Tiller in drive position $h14$ (in) $35.0$ raw Chassis height $h10$ (in) $7.0 \times 8.6 \times 10.2$ overall length $h10$ (in) $7.0 \times 8.6 \times 10.2$ overall length $b1$ (in) $66.7$ overall width $b1$ (in) $28.4$ overall width $b1$ (in) $28.4$ overall speed $m2$ (in) $3.9$ urning radiusWa (in) $50.8$ ravel SpeedUnladenmphravel SpeedUnladenMrawbar pull (max)Laden/UnladenNrake $i$ $i$ attery Voltage $v/Ah$ $24/80$ attery Voltage $L \times W \times H$ inattery Dimensions $L \times W \times H$ inattery Compartment Size $i$ $i$	Axle loading, unladen	Rear	lbs	94.6
Wheels, number front/rear (x=drive wheels)   Image: Stream of the stream of	īre Size	Front, pneumatic		16 x 6.5-8.00
readFrontb10 (in)21.9eight of Tiller in drive positionh14 (in)35.0raw Chassis heighth10 (in)7.0 x 8.6 x 10.2overall lengthl1 (in)66.7overall widthb1 (in)28.4overall widthb1 (in)28.4overall widthm2 (in)3.9urning radiusWa (in)50.8ravel SpeedLadenmph3.0ravel SpeedUnladenmph3.4rawbar pull (max)Laden/UnladenN300rakeoverallN1000rakelbs107.8attery VoltageLx W x Hin10.2 x 6.7 x 8.5ype of Drive ControlLx W x Hin10.6 x 7.0 x 8.9				5.0
line independence leight of Tiller in drive positionh14 (in)35.0irraw Chassis heighth10 (in) $7.0 \times 8.6 \times 10.2$ irraw Chassis heightl1 (in) $66.7$ overall lengthl1 (in) $28.4$ overall widthb1 (in) $28.4$ oround clearancem2 (in) $3.9$ urning radiusWa (in) $50.8$ ravel SpeedLadenmphravel SpeedUnladenmphravel SpeedLaden/UnladenNorawbar pull (max)Laden/UnladenNrakeorelectricattery Voltagev/Ah24/80attery Weightlbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ope of Drive Controlin10.6 x 7.0 x 8.9	Wheels, number front/rear (x=driv	e wheels)		2x/1
rraw Chassis height h10 (in) 7.0 x 8.6 x 10.2   overall length l1 (in) 66.7   overall width b1 (in) 28.4   oround clearance m2 (in) 3.9   urning radius Wa (in) 50.8   ravel Speed Laden mph 3.0   ravel Speed Unladen mph 3.4   rawbar pull (max) Laden/Unladen N 300   rake ov/Ah 24/80 electric   attery Voltage L x W x H in 10.2 x 6.7 x 8.5   ope of Drive Control L x W x H in 10.6 x 7.0 x 8.9	Tread		b10 (in)	21.9
Averall length   I1 (in)   66.7     overall width   b1 (in)   28.4     oround clearance   m2 (in)   3.9     urning radius   Wa (in)   50.8     ravel Speed   Laden   mph   3.0     ravel Speed   Unladen   mph   3.4     orawbar pull   Laden/Unladen   N   300     orawbar pull (max)   Laden/Unladen   N   1000     rake   v/Ah   24/80   electric     attery Voltage   Lx W x H   in   10.2 x 6.7 x 8.5     ope of Drive Control   Lx W x H   in   10.6 x 7.0 x 8.9	Height of Tiller in drive position	on	h14 (in)	
by erall width   b1 (in)   28.4     irround clearance   m2 (in)   3.9     urning radius   Wa (in)   50.8     ravel Speed   Laden   mph   3.0     ravel Speed   Unladen   mph   3.4     irrawbar pull   Laden/Unladen   N   300     irrawbar pull (max)   Laden/Unladen   N   1000     rake   Image: Speed   v/Ah   24/80     attery Voltage   Lx W x H   in   10.2 x 6.7 x 8.5     ype of Drive Control   Image: Speed   Image: Speed   Image: Speed	Draw Chassis height		h10 (in)	7.0 x 8.6 x 10.2
iround clearancem2 (in)3.9urning radiusWa (in)50.8ravel SpeedLadenmph3.0ravel SpeedUnladenmph3.4rawbar pullLaden/UnladenN300rawbar pull (max)Laden/UnladenN1000rakeImage: State sta	Overall length		l1 (in)	66.7
urning radiusWa (in)50.8ravel SpeedLadenmph3.0ravel SpeedUnladenmph3.4rawbar pullLaden/UnladenN300rawbar pull (max)Laden/UnladenN1000rakeelectricattery Voltagev/Ah24/80attery WeightLx W x Hin10.2 x 6.7 x 8.5ype of Drive Controlmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Overall width		b1 (in)	28.4
ravel SpeedLadenmph3.0ravel SpeedUnladenmph3.4rawbar pullLaden/UnladenN300rawbar pull (max)Laden/UnladenN1000rakeelectricattery Voltagev/Ah24/80attery WeightIbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlin10.6 x 7.0 x 8.9	Ground clearance		m2 (in)	
ravel SpeedUnladenmph3.4rrawbar pullLaden/UnladenN300rawbar pull (max)Laden/UnladenN1000rakeIIelectricattery Voltagev/Ah24/80attery WeightIbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlin10.6 x 7.0 x 8.9	Turning radius		Wa (in)	50.8
Laden/UnladenN300rawbar pull (max)Laden/UnladenN1000rakeN1000electricattery Voltagev/Ah24/80attery WeightIbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlin10.6 x 7.0 x 8.9	Fravel Speed	Laden	mph	3.0
trawbar pull (max)Laden/UnladenN1000rake0electricattery Voltagev/Ah24/80attery Weightlbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlomosfetmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Travel Speed	Unladen	mph	3.4
rakeImage: constraint of the systemelectricattery Voltagev/Ah24/80attery WeightIbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlmosfetmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Drawbar pull	Laden/Unladen	Ν	300
attery Voltagev/Ah24/80attery Weightlbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlmosfetmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Drawbar pull (max)	Laden/Unladen	Ν	1000
attery WeightIbs107.8attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Brake			electric
attery DimensionsL x W x Hin10.2 x 6.7 x 8.5ype of Drive Controlmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Battery Voltage		v/Ah	24/80
ype of Drive Controlmosfetattery Compartment Sizein10.6 x 7.0 x 8.9	Battery Weight		lbs	107.8
attery Compartment Size in 10.6 x 7.0 x 8.9	Battery Dimensions	$L \times W \times H$	in	10.2 x 6.7 x 8.5
	Type of Drive Control			mosfet
ervice Weight with battery lbs 370	Battery Compartment Size		in	10.6 x 7.0 x 8.9
ins 550	Service Weight with battery		lbs	330

**Superlift Material Handling Inc** 23 - 500 Fairway Rd S Suite 402 Kitchener, ON N2C 1X3

**Superlift Material Handling Inc** 23 - 500 Fairway Rd S Suite 402 Kitchener, ON N2C 1X3

# **Electric Puller**

### **ELECTRIC PULLER** 3,300LB